


# PAREX THERM ONTO TIMBER FRAME

WALL VENT



# PTTNC0714A

This detail is for general guidance only and is not project specific. Always refer to the project architect details and the PAREX project specific specification.



Timber frame structure  
At 400mm centres  
(by others)

Insulation  
(by others)

Sheathing board  
(by others)

Parex WeatherTech  
Weatherseal or  
proprietary breath  
membrane  
(by others, if required)

Resistant Multi-Rend  
render board

PAREX THERM render  
system incorporating  
355 AVU mesh

Min 200mm x 200mm  
Lamella insulation  
surrounding the vent  
pipe as detailed on  
the Parex specification

uPVC vent pipe and  
surface grill  
(by others)

**PAREX**

System: PAREX THERM onto Timber Frame

Application: PAREX THERM system onto Resistant Multi-Rend render board – Wall vent

Drawing No: PTTNC0714A (In addition to this detail please also refer to detail – PTTNC0714B)

Date: June 2016

**PAREX**

The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not covered by this document are used, customers must request specific additional information and/or carry out a representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.